

PRODUCT INFORMATION



SOLID[®] LAMINBOARD

SOLID Double Deck 5 Layers

Deck	HDF
Core	3 mm strips of spruce or poplar wood
Underdeck	fromager
Glue	AW 100
Emission class	E1
Format	5200 x 2070 mm
Thickness	16/19/mm
	Other thicknesses available on request
Max. press format	2200 x 6300 mm
Moisture content	8 – 12%
Tolerance in thickness	+ 0,2 mm – 0,6 mm
Tolerance in length and width	± 2 mm/m
Squareness tolerance	1 mm/m

Thickness in mm	E-Modul (N/mm ²) (length)	E-Modul (N/mm ²) (width)	Bending strength (N/mm ²) (length)	Bending strength (N/mm ²) (width)
16	3427	3786	40	36
19	10376	8288	81	67

Multiple applications

HS Baco Panels offers the most suitable blockboard for each application.

A wide range of surface and cores ensure various alternatives. Additionally we develop solutions together with our customers, according to their individual requirements.

Significant advantages

- High stability and moisture resistance
- High bending strength
- Light weight
- High screw extraction resistance
- Easy processing

High quality

High quality raw material and longtime experience of our team are the basis for the outstanding quality of our blockboards.

Continuous quality controls ensure stable standards.

All wood that is processed by HS Baco Panels comes from PEFC™ controlled sources.